## SERVICE INFO

Page 1/2

### Hydraulic tensioning unit conversion kit 533 0097 10 and mechanical tensioning arm 533 0015 10 for BMW

Vehicle

Manufacturer: BMW

**Models:** E34, E36, E38, E39,

E46, E53, E60, E61, E65, E66, E83, Z3, Z4

**Engines:** 

**E34** 520, 525

**E36** 320, 323, 325, 328

**E38** 728

**E39** 520, 523, 525, 528, 530

**E46** 320, 323, 325, 328, 330

**E53** 3.0

**E60** 520, 525, 530

**E61** 520, 525, 530

**E65** 730

**E66** 730

**E83** 2.5, 3.0

**Z3** 2.0, 2.2, 2.8, 3.0

**Z4** 2.2, 2.5, 3.0

OE Nos.:

11 28 1 427 252 (mech.)

11 28 1 735 899 (mech.)

11 28 1 748 832 (mech.)

Part Nos.:

533 0015 10 (mech.) 533 0097 10 (hydr.)



**Image 1:** 533 0015 10 (mechanical design)



**Image 2:** 533 0097 10 (hydraulic design)

The mechanical tensioning arm 533 0015 10 (Image 1) in the original equipment has been replaced by a tensioner with hydraulic damping (Image 2).

As an alternative, Schaeffler Automotive Aftermarket offers a conversion kit 533 0097 10 that, in addition to the hydraulic damper, contains all the necessary components required to convert from the mechanical to the hydraulic tensioner (Image 3).



**Image 3:** 533 0097 10 — Scope of delivery

The package includes the relevant assembly instructions that illustrate how the components must be assembled.


#### Note:

Page 2 of this Service Information sheet shows the correct installation positions of the two tensioner designs.


# SERVICE INFO

Page 2/2

## Hydraulic tensioning unit conversion kit 533 0097 10 and mechanical tensioning arm 533 0015 10 for BMW



**Image 4:** Installation position of the mechanical tensioning arm



**Image 5:** Installation position of the hydraulic conversion kit 533 0097 10 with all the relevant components

### Key to image 4:

- (1) Holder on engine block\*
- (2) Tensioning arm 533 0015 10
- (3) Fixing bolts M8x35\*

### Key to image 5:

- (1) Holder on engine block\*
- (2) Tensioning arm 534 0009 10
- (3) Washer M8x21x2 mm
- (4) Bolt M8x105 mm
- (5) Cover 30x4.2 mm
- (6) Bolt M8x35 mm
- (7) Washer M8x21x2 mm
- (8) Bolt M8x50 mm
- (9) Plate M10x40x1.5 mm
- (10) Deflection pulley 532 0001 10
- (11) Bolt M10x25 mm
- (12) Cover 55x5 mm

#### Note:

Note that different mounting holes must be used for the mechanical and hydraulic tensioner designs in order to ensure correct operation.

\*) Not included with part or kit+

Appropriate spare parts can be found in our on-line catalogue at www.Schaeffler-Aftermarket.com or in RepXpert at www.RepXpert.com.

Issued 04.2010

(replaces 08.2009)

Subject to technical changes
© 2010 Schaeffler Automotive Aftermarket

#### For further information:

Info@LuK-AS.co.uk

Phone: +44 (0) 14 32 264 264\* Fax: +44 (0) 14 32 375 760

www.Schaeffler-Aftermarket.com
\* Calls from within the UK 08457 001100

