



# VKBA 3637

Technical Bulletin – September 2015

VKBA 3637



Renault: Modus, Logan I, Megane II, Clio II, Clio Grandtour, Kangoo ----> 2002-11-01

Nissan: Micra III --> 2003-01-01

Dacia: Sandero, Logan ----> 2008-11-01



Mandatory placement of the ABS sensor holder in the center of the knuckle



**OE Nb:** Renault/Dacia: 77 01 207 677, 60 01 550 915, 40 21 057 33R  
Nissan: 40210-1HA1A, 40210-AX000

VKBA 3637



The wheel bearing kit VKBA 3637 has an ABS sensor holder included as a part of several accessories contained in the kit.



picture 1

## Correct mounting

The ABS sensor holder is placed centered, cannot damage the bearing and the ABS sensor will generate an accurate signal.



picture 2

## Wrong mounting

The ABS sensor is **NOT** placed centered, which causes a deformation of the ABS sensor holder and an abrasion of the ABS sealing. This could lead to a premature bearing failure and ABS signal problems (see pictures to the right).

## Mounting of the ABS sensor holder

When mounting the ABS sensor holder, it is mandatory to place it in the center of the knuckle, before pressing in the bearing (see *picture 1*). A wrong position of the holder causes an abrasion of the ABS sealing and leads to premature bearing failure due to the deformation of the ABS holder (see *picture 2*).



Install confidence  
[www.vsm.skf.com](http://www.vsm.skf.com)